



MATERIAL SAFETY DATA SHEET

GeLavish Prime-It

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: GeLavish Prime-It
CHEMICAL NAME: Primer
CHEMICAL FAMILY: Nail Primer
PRODUCT USE: Adhesion Improvement
EMERGENCY PHONE: Info-Trac 1-352-323-3500
MSDS DATE: 3/5/2011

MANUFACTURER: International Nail Manufacturers (inm)
DIVISION: Nail Cartel, Inc.
ADDRESS: 1221 N. Lakeview Ave.
PHONE: 714-779-9892
FAX: 714-779-9971
PREPARED BY: Garret Kellenberger-Production Manager

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA
Ethyl Acetate	141-78-6	205-500-4	Ethyl Acetate	400 ppm	400 ppm	Not Listed
2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy) BIS-GMA	1565-94-2	216-367-7	Isopropylidenediphenyl bisoxyhydroxypropyl methacrylate	N/E	N/E	Not Listed
2-Hydroxy ethyl methacrylate	868-77-9	212-782-2	HEMA	N/E	N/E	Not Listed

N/E-None Established
 N/R-Not Reviewed

N/DA-No Data Available
 N/A-Not Applicable

Ethyl Acetate: Hazard Symbol-F,Xi Risk Phrases-R11, R36, R66, R67 Safety Phrases-S2, S16, S26, S33
2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy)BIS-GMA: Hazard Symbol-N/E Risk Phrases-N/E Safety Phrases-N/E
2-Hydroxy ethyl methacrylate: Hazard Symbol-Xi Risk Phrases-R36/38, R43 Safety Phrases-S2, S26, S28

See Section 16 for Risk and Safety Phrase Key

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This information is based on finding from related or similar materials.

- **May cause eye irritation.**
- **Flammable liquid and vapor.**
- May cause skin irritation.
- Avoid prolonged or repeated breathing of gases, vapors, or mists.
- Unstable (reactive) upon depletion of inhibitor. This is only a slight risk.
- May be absorbed through the skin.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: Inhalation, skin contact, eye contact.
Eyes: Exposure causes eye irritation. Symptoms include stinging, tearing, redness and swelling.
Skin: Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying, cracking, and skin burns.
Ingestion: Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.
Inhalation: Vapor and mist are irritating to mucous membranes. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.
Sub-Chronic Effects: May cause headaches, nausea, vomiting and narcotic effect if over-exposed.
Chronic Health Effects: No appropriate human or animal health effects data are known to exist.
(Long Term)

NOTE: Refer to Section 11, Toxicological Information for Details

SECTION 4: FIRST AID MEASURES

First Aid for Eye: If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently for 15 min. with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.



MATERIAL SAFETY DATA SHEET

GeLavish Prime-It

First Aid for Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention.

First Aid for Ingestion: If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

First Aid for Inhalation: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point (°F/°C)	Flammable Limit (vol %)	Auto-ignition Temperature (vol %)
TAG Closed: 26°F/-3.3°C	400 ppm	750°F-900°F

Method:

Extinguishing Media: Foam, dry chemical, cold water spray.

Fire Fighting Instructions: Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Water spray may be used to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location.

Unusual Hazards: Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may product toxic products CO, Carbon Dioxide. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill or Release Procedures: Eliminate all sources of heat and ignition. Use an absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e.g. vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

SECTION 7: HANDLING AND STORAGE

Handling: Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash skin thoroughly after handling.

Storage: Store in a well ventilated area. Store @ 70+15°F, allow some air space above liquid level. Keep containers closed while not in use.

Explosion Hazard: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Facilities storing or utilizing this material should be equipped with an eye facility and a safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Personal Protective Equipment

General: To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR 1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/Face Protection: Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of safety glasses.

Skin Protection: Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits.



MATERIAL SAFETY DATA SHEET

GeLavish Prime-It

Protection provided by air purifying respirators is limited. Wear A NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN 149.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Odor & Odor Threshold	pH	VOC (g/L)	Specific Gravity	Viscosity	% Volatile
Clear liquid	Ester like odor	NA	736	(H ₂ O=1):0.92	15 cps	W/W%:50+

Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure	Vapor Density	Evaporation Rate	Ignition	Solubility in Water
N/DA	N/DA	N/DA	N/DA	(Air=1):1	NA	NA	Insoluble

Flash Point (°F/°C)	Flammable Limit (vol %)	Auto-ignition Temperature (vol %)
TAG Closed: 26°F/-3.3°C	400 ppm	750°F-900°F

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable

Incompatibility (Materials to Avoid) Avoid oxidizing agents Acids, and bases (heat).

Hazardous Decomposition Products:
Heated material produces NO₂, CO₂, CO

Hazardous Polymerization: May occur

Conditions to Avoid: Heat, flame, ignition sources.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation-Skin	Irritation-Eye
Oral LD ₅₀ (rat):4.0-6.0g/kg	Dermal LD ₅₀ (rabbit): >20mL/kg	Inhalation LC ₅₀ (rat): 3500-8000 ppm/4 hours	Rabbit: slight	Rabbit: slight

Since this product contains a mixture of active components, the primary toxicological information is derived from the acetates. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-Chronic Toxicity
N/DA	E.Coli: NDA Damage: 20mol/L	N/DA

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of diking material and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state, and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.



MATERIAL SAFETY DATA SHEET

GeLavish Prime-It

SECTION 14: TRANSPORT INFORMATION

DOT (49 CFR 172)	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, monomers), 3, PGII
Identification #	UN1993
Marine Pollutant:	No
Special Provisions:	T8, T31
Emergency Response Guidebook (ERG) #	128
IATA (DRG)	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s. (ethyl acetate, monomers) ,3, PGII
Class or Division:	3
UN or ID Number:	UN1993
Packaging Instructions:	A3
Emergency Response Guidance (ICAO) #:	3L
IMO (IMDG)	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s. (ethyl acetate, monomers), 3, PGII
Class or Division:	3.2
UN or ID Number	UN1993
Special Provisions & Stowage/Segregation	None
Emergency Schedule (EmS) #:	307
Other Information	Flash point = -3.3°C

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clear Air Act: <ul style="list-style-type: none"> NONE There are no ODS substances in this product.
Clean Water Act: Priority Pollutant	This product contains the following chemicals listed under the U.S. Clean Water Act Hazardous Substance List: <ul style="list-style-type: none"> NONE The following chemicals are listed as primary pollutants: <ul style="list-style-type: none"> NONE
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> IMMEDIATE (ACUTE) HEALTH HAZARD FIRE HAZARD
RCRA	This product contains the following chemicals considered to be hazardous waste under RCRA (40 CFR 261): <ul style="list-style-type: none"> Ethyl Acetate CAS #141-78-6 , RCRA Code: U112
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances.
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): <ul style="list-style-type: none"> Ethyl Acetate, CAS #141-78-6, RQ (Lbs) :5000
SARA Title III: Section 311-312	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> IMMEDIATE (ACUTE) HEALTH HAZARD FIRE HAZARD REACTIVE HAZARD
SARA Title III: Section 313	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.
TSCA Section 8 (b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6
NJ Right-to-Know Law:	Ethyl Acetate CAS #141-78-6



MATERIAL SAFETY DATA SHEET

GeLavish Prime-It

PA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6
FL Right-to-Know Law:	Ethyl Acetate CAS #141-78-6
MN Right-to-Know Law:	Ethyl Acetate CAS #141-78-6

SECTION 15: REGULATORY INFORMATION-cont.

International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Ethyl Acetate CAS #141-78-6 is on the DSL List. WHMIS = B2, D2B 2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy)BIS-GMA CAS #1565-94-2 is n/da for the DSL List. WHMIS = n/da 2-Hydroxyethyl methacrylate CAS #868-77-9 is on the DSL List. WHMIS = n/da
EINECS: European EInventory	Gelavish Prime-It: <ul style="list-style-type: none"> Hazard Symbols: Xi, F Risk Phrases: R11: highly flammable, R36: Irritating to eyes, R43: May cause sensitization by skin contact, R66: repeated exposure may cause skin dryness and cracking, R67: Vapors may cause drowsiness and dizziness. Safety Phrases: S16: keep away from sources of ignition-no smoking, S26: in case of contact with eyes, rinse immediately, S28A: after contact with skin, wash immediately with plenty of water, S33: take precautionary measures against static discharges. S36/37: Wear suitable protective clothing and gloves.



SECTION 16: OTHER INFORMATION

Hazard Symbol:

F-Flammable substances or preparations
Xi-Irritants

Risk Phrases:


R11: Highly flammable; R36 Irritating to eyes; R36/38 Irritating to eyes and skin; R43 May cause sensitization by skin contact; R66 Repeated exposure may cause skin dryness or cracking; R67 Vapors may cause drowsiness and dizziness.

Safety Phrases:

S2 Keep out of reach of children; S16 Keep away from sources of ignition-No Smoking; S26 In case of contact with eyes; rinse immediately with plenty of water and seek medical advice; S28 After contact with skin, wash immediately with plenty of water; S33 Take precautionary measures against static discharges.

Hazard Rating System (Pictograms)

NFPA:



HMIS:

2	Health
1	Flammability
2	Reactivity

DISCLAIMER: The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.



GeLavish Prime-It

